

Fact Sheet

Vivago POINT base stations product family

The building will be equipped with Vivago POINT base stations, allowing wireless alarms to be triggered from anywhere in the building. The base stations can be used in different configurations to implement the functionality of the Vivago system.

Vivago Viva POINT – General base station

Features

Supported Vivago RF-devices: CARE 800x watches, FIDO, DI-2-x IP

Transfer of activity data and alarms

Automatic self-diagnostics & FOTA updates

Available in six hardware configurations for flexible installation



Vivago Viva POINT

Technical specifications

	Viva POINT	Viva POINT 4G	Viva POINT w. Batt
Weight	~210 g	~310 g	~290 g
Internet connection	Ethernet	4G	Ethernet
Interfaces	Ethernet 100Mbit/s, Vivago RF, Status indicator LED	4G (LTE), Ethernet 100Mbit/s, Vivago RF, Status indicator LED	Ethernet 100Mbit/s, Vivago RF, Status indicator LED
Power Supply	PoE (24W) with PoE adapter Device input: 2A/12V DC	Input: 100-240 V 50/ 60Hz AC Device Input: 2A/12V DC Wall plug options: Type C & Type G (Euro & UK)	
Back-up power	Via PoE	Rechargeable Battery, 5000mAh, LiPo	
Dimensions (W x L x H)	173 x 131 x 46 mm		
Case Material / Color	ABS / White		
Operating conditions	Operating temperature: 5 - 40°C, RH% 0-80 (indoor use only)		
Storage temperature	-15 - 50°C, RH% 0-80		
Degree of protection	IP20		
Available as Plus-version	Plus version enables additional hardware capabilities.		

Order codes and configurations

Vivago code	Type	Description	Notes
EU000062035	Viva POINT	General base station for institutions	Powered by PoE adapter
EU000062031	Viva POINT 4G	General 4G base station for institutions	Requires SIM card
EU000062033	Viva POINT w. Batt	General base station for institutions, with battery	

Recommended Mobile subscription for 4G configuration

4G/ LTE, Minimum data plan 2GB per month

Data rate from 2Mbit/sec

SIM card: Nano-SIM (4FF)

Marketing restriction, secret mobile phone number, answering service removed, PIN-code query disabled, IMEI lock recommended

Vivago

Fact Sheet

Vivago POINT base stations product family

Vivago Go POINT – Wandering Control base station

Features

Supported Vivago RF-devices: CARE 800x watches, FIDO, DI-2-x IP

Transfer of activity data and alarms

Automatic self-diagnostics & FOTA updates

Wandering control (requires CARE 8005 watch) [SPECIFIC FOR THIS CONFIGURATION](#)

Functions also as a general base station

Relay input

Zigbee interface for wireless peripherals (door sensors, etc)

Available in six hardware configurations for flexible installation



Vivago Go POINT

Technical specifications

	Go POINT	Go POINT 4G	Go POINT w. Batt
Weight	~210 g	~310 g	~290 g
Internet connection	Ethernet	4G	Ethernet
Interfaces	Ethernet 100Mbit/s, Vivago RF, Relay in, Status indicator LED	4G (LTE), Ethernet 100Mbit/s, Vivago RF, Relay in, Status indicator LED	Ethernet 100Mbit/s, Vivago RF, Relay in, Status indicator LED
Power Supply	PoE (24W) with PoE adapter Device input: 2A/12V DC	Input: 100-240 V 50/ 60Hz AC Device Input: 2A/12V DC Wall plug options: Type C & Type G (Euro & UK)	
Back-up power	Via PoE	Rechargeable Battery, 5000mAh, LiPo	
Dimensions (W x L x H)	173 x 131 x 46 mm		
Case Material / Color	ABS / White		
Operating conditions	Operating temperature: 5 - 40°C, RH% 0-80 (indoor use only)		
Storage temperature	-15 - 50°C, RH% 0-80		
Degree of protection	IP20		
Available as Plus-version	Plus version enables additional hardware capabilities.		

Order codes and configurations

Vivago code	Type	Description	Notes
EU000062045	Go POINT	Wandering control base station for institutions	Powered by PoE adapter
EU000062041	Go POINT 4G	Wandering control 4G base station for institutions	Requires SIM card
EU000062043	Go POINT w. Batt	Wandering control base station for institutions, with battery	

Recommended Mobile subscription for 4G configuration

4G/ LTE, Minimum data plan 2GB per month

Data rate from 2Mbit/sec

SIM card: Nano-SIM (4FF)

Marketing restriction, secret mobile phone number, answering service removed, PIN-code query disabled, IMEI lock recommended

Vivago

Fact Sheet

Vivago POINT base stations product family

Vivago Room POINT – Base station with a voice connection for room specific needs

Features

Supported Vivago RF-devices: CARE 800x watches, FIDO, DI-2-x IP

Transfer of activity data and alarms

Automatic self-diagnostics & FOTA updates

Voice connection between nurse and customer

Activation of nurse presence or alarm with optional remote control

Support for different room states:

Active alarm

Nurse in/ out

Additional help request

Corridor lights can be controlled according to room state

Functions also as a general base station

Zigbee interface for wireless peripherals (e.g. remote control)

Relay input for wired alarm device connection


SPECIFIC FOR THIS CONFIGURATION



Vivago Room POINT



Speaker



Remote control

Technical specifications

	Room POINT	Speaker (Jabra Speak 510 utilised)
Dimensions	173 (W) x 131 (L) x 46 (H) mm	Diameter 120 mm, 33 mm (H), speaker cord length 900 mm
Weight	~310 g	~175 g
Internet connection	4G	-
Back-up power	Rechargeable Battery, 5000mAh, LiPo	Battery included (Lithium-Ion)
Interfaces	4G (LTE), Ethernet 100Mbit/s for data only, USB for speaker connection, Vivago RF, Relay in, Zigbee, Status indicator LED	USB-connected to base station, Status indicator LEDs
Case material / Color	ABS / White	Black
Voice communication	Cellular calls via mobile network, VoLTE call support	
Power Supply	Input: 100-240 V AC, Device input: 2A/12V DC, Plug options: Type C & Type G (Euro & UK)	
Operating conditions	Operating temperature: 5 - 40°C, RH% 0-80 (indoor use only)	
Storage temperature	-15 - 50°C, RH% 0-80	
Degree of protection	IP20	

Available as Plus-version Plus version enables additional hardware capabilities.

Order codes and configurations

Vivago code	Type	Description	Notes
EU000062011	Room POINT 4G	For care rooms with voice connection	Speaker included, Requires SIM card

Key Accessories

EU000062201	Holder for Vivago POINT USB speaker
EU000062021	Remote control

Recommended Mobile subscription

4G/ LTE, Minimum data plan 2GB per month
Voice calls with VoLTE support recommended
Data rate from 2Mbit/sec
SIM card: Nano-SIM (4FF)

Marketing restriction, secret mobile phone number, answering service removed, PIN-code query disabled, IMEI lock recommended

Fact Sheet

Vivago POINT base stations product family

Vivago Domi POINT – Central unit of Vivago Domi home solution



Features

Supported Vivago RF-devices: CARE 8001 watch, FIDO, DI-2-x IP

Support for 1 CARE watch or FIDO

Transfer of activity data and alarms

Automatic self-diagnostics & FOTA updates

Voice connection between nurse and customer

Activation of nurse presence or alarm with optional remote control

Support for different room states:

Active alarm

Nurse in/ out

Additional help request

Zigbee interface for wireless peripherals (e.g. remote control)


Relay input for wired alarm device connection



Vivago Domi POINT



Speaker



Remote control

SPECIFIC FOR THIS CONFIGURATION

Technical specifications

	Domi POINT	Speaker (Jabra Speak 510 utilised)
Dimensions	173 (W) x 131 (L) x 46 (H) mm	Diameter 120 mm, 33 mm (H), speaker cord length 900 mm
Weight	~310 g	~175 g
Internet connection	4G	
Back-up power	Rechargeable Battery, 5000mAh, LiPo	Battery included (Lithium-Ion)
Interfaces	4G (LTE), Ethernet 100Mbit/s for data only, USB for speaker connection, Vivago RF, Relay in, Zigbee, Status indicator LED	USB-connected to base station, Status indicator LED
Case material / Color	ABS / White	Black
Voice communication	Cellular calls via mobile network, VoLTE call support	
Power Supply	Input: 100-240 V AC Device input: 2A/12V DC Plug options: Type C & Type G (Euro & UK)	
Operating conditions	Operating temperature: 5 - 40°C, RH% 0-80 (indoor use only)	
Storage temperature	-15 - 50°C, RH% 0-80	
Degree of protection	IP20	
Available as Plus-version	Plus version enables additional hardware capabilities.	

Order codes and configurations

Vivago code	Type	Description	Notes
EU000062054	DOMI POINT 4G w. CARE 8001	For home environment with voice connection	Speaker included Requires SIM card

Key Accessories

EU000062201	Holder for Vivago POINT USB speaker
EU000062021	Remote control

Recommended Mobile subscription

4G/ LTE, Minimum data plan 2GB per month
Voice calls with VoLTE support recommended
Data rate from 2Mbit/sec
SIM card: Nano-SIM (4FF)
Marketing restriction, secret mobile phone number, answering service removed, PIN-code query disabled, IMEI lock recommended